
### **SCHAEFFLER**


We pioneer motion

### OPTIME C1

The world's first smart lubricator



LUBRICATION WORKLOADS UNTILNOW



The job of manually managing lubrication across a production line, factory hall or plant is filled with all sorts of repetitive tasks that steal time employees could put to better use elsewhere. Nevertheless, these tasks are necessary. Downtime triggered by inadequate machine lubrication is both common and expensive. It creates a situa-

tion that puts valuable machines at risk. Given the number of components that have to be checked and the number of different cartridge replacements required, the task of monitoring machines is virtually a full-time job – until now, that is!



We are proud to present the world's first smart lubricator. It is a device that streamlines lubrication management via alerts sent by a mobile app or web-based dashboard. It is also a product based on the three principles of our OPTIME philosophy:



#### Transparency

The solution enables your maintenance team to monitor all lubrication points regardless of location – on site, in the office, at home, or even on the other side of the world.



### **Simplicity**

Plug-and-play functionality means that all the guesswork is taken out of installation and operation. You pick it up, you screw it on, and when you get an alert, you replace the lubrication cartridge. Simple and scalable!



### Uptime

Lubrication avoids dreaded production line downtime and helps you fulfill orders and keep things moving with as little manual work as possible.
Work smart, not hard!



# Customer Success Story: Simplification in action

Founded in 1916, this German company is a manufacturer of high-quality ceramic products for buildings as well as vitrified clay pipes for the water and wastewater industry.


Our work with this company enabled it to avoid mill failures that generate costs of EUR 47,000 – all in a factory environment where components operate at up to 1,200°C.

The smart functionality in the device warned them of any impending lubrication shortage, saving them time and money.

When I open the app and see that everything is running smoothly, it gives me peace of mind.

Peter Hannappel Maintenance Manager Westerwälder Elektro Osmose

### So how does it work?




### Challenge? Accepted.


You may have trouble imagining how a product like OPTIME C1 could fit into your workflow. Here are three common ways that our award-winning solution can help you:



# You have hundreds of lubrication points that need constant monitoring

You can bid farewell to those days when your maintenance team checked the lubrication status of machinery on a daily or weekly basis. All you have to do now is connect OPTIME to the IIoT. You will then have component status and fill-level information at your fingertips. But that is hardly all. Should a malfunction occur, automatic alarms will be sent to you.





### **Group view**

Our solution creates clear groups for your machines and lubrication points — a feature that lets you keep an eye on every one of those lubrication points.


### "All lubricators" group view

All lubrication points within the groups are sorted by urgency. You will always know which lubricator needs your attention next.

Easy-to-understand information is provided about critical lubricant-filling levels, high temperatures, and high pressures. You immediately know what the problem is — and can act accordingly.

# Your maintenance team does not know which lubricant cartridge to use

Eliminate manual errors from your lubrication workflow. Thanks to its intuitive screw-on functionality, OPTIME C1 prevents incorrect cartridges from being installed and dispensing lubricant – hindering expensive damage in the process.





### Replace lubricant cartridge


The solution provides assisted input about lubrication parameters, lubricant quantity and time period. You can use this vital information to correctly set up each of your lubricators correctly.

### Scan QR code

Scan the QR code on the cartridge to ensure that you are using the right lubricant at the right lubrication point.

## You want to get started, but don't know how

We have designed OPTIME C1 to be as easy to install as possible. Its plug-and-play functionality facilitates seamless scalability and does not require extensive worker training. Our lubrication management system will also eliminate the need for costly new bearings – great news for your profit margins.



### **Provisioning lubricator**

A simple NFC scan of the OPTIME C1 activates and configures it. This ensures that you can save your resources for more important tasks.





## Feature rich, cost efficient

### Product specifications

Description		Value	Unit
OPTIME C1 fund	ction		
Drive system		Electro-mechanical	-
Operating pressure		<10	bar
Metering volume per lubrication interval		0.5	cm³
Metering volume per day (dependent on size and setting of CONCEPT1)		0.17 up to 8.3	cm³
Commissioning		NFC	-
CONCEPT1 lubr	icator		
Dispensing time (steplessly adjustable)		1 up to 12	months
Lubricant volume		60 or 125	cm³
Lubricant	Grease	⟨NLGI 2	_
	Oil	> 68	cSt
Communication	<u> </u>		
Wirepas Mesh (ISM band)		2.4	GHz
Range with line of sight		100	m
Electrical chara	cteristics		
Power supply (battery pack)		6	V
		2.3	Ah

### Our key features at a glance:

- Status and fill-level information available via the OPTIME app or desktop dashboard
- Automatic alarm notification in the case of an adverse event
- Simple installation and maintenance
- Ability to adjust each lubricator individually
- Optimized maintenance and routing
- Pressure allowance of up to 10 bar
- Rapid and easy screw-on cartridge replacement
- User guidance available in several languages

Description		Value	Unit
Other characteristics			
Mounting position		As required	-
Threaded connector		G1/4	_
Housing material		PET	_
Mass		= 0.25	kg
Warranty and operating life	Duration	2	years
	Number of emptying operations	10	_
Packing unit		10	pieces
Ambient conditions		IDC0	
Protection class		IP68	_
Operating temperature		– 10 up to + 55	°C
Storage (protect from direct sunlight, store	Temperature (recommended)	+20±5	°C
in a dry place)	Humidity	<65	%
Certificates			
CE Radio Equipment Directi	ve 2014/53/EU	_	_



An adapter allows the OPTIME C1 to be used with certain lubrication devices from other manufacturers (see page 13).

## Technical data — gateway

Description		Value	Unit
Communication			
Wirepas Mesh (ISM band)		2.4	GHz
2G, LTE CAT M1 (additional options with installed local LTE stick)		-	-
Wi-Fi		2.4	GHz
Ethernet RJ45		-	-
SIM card format		Micro SIM (3FF)	-
Electrical characte	eristics		
Power consumption		30	VA
AC power supply		85 up to 264	V
Frequency		47 up to 440	Hz
Ambient condition Protection class	ns	IP66	_
Operating temperature		-20 up to +50	°C
Storage	Temperature	-40 up to +85	°C
	Humidity	20 up to 90	%
Dimensions, mass	s		
Length		180	mm
Width		130	mm
Height		81	mm
Mass		=1.2	kg
Certificates			
CE Radio Equipment Directive 2014/53/EU		-	-

# A proud member of the OPTIME Ecosystem – OPTIME C1



Launched in 2020 and developed for the condition monitoring of entire plants and production facilities: the OPTIME Ecosystem makes simple, effective predictive maintenance affordable for the process industry.

The addition of the world's first truly smart lubricator – the OPTIME C1 – in 2021 expanded the portfolio to make smart lubrication management possible for the first time.

www.schaeffler.de/en/optime-ecosystem



### Life is unfair

Depending on the assets you already own or the contracts you inherited from your predecessor. You might not always have the possibility to switch to a smarter way of working — and that puts you at a disadvantage. But it doesn't have to be that way.

### Not when it comes to lubrication. Not with Schaeffler.

With the new **OPTIME C1 adapter,** you can now quickly transform your existing gas-driven single point lubricators into smart lubricators — and enjoy all the benefits of smart lubrication that others do. It's only fair.

### Cartridge compatibility

Cartridge sizes: 60 ml, 125 ml

#### Compatible with

- perma-tec: FLEX, FLEX PLUS, NOVA
- SKF: System 24 LAGD
- NTN: READY BOOSTER, SMART BOOSTER
- Klüber: KlübermaticFLEX, KlübermaticNOVA

### Material number

301271968-0000-10

### **SCAN TO CONTACT US**



### **SCAN TO BUY NOW**



# EASY INEVERY WAY

Based on Schaeffler's long-standing expertise in the fields of bearing engineering, vibration analysis, and lubrication: the OPTIME Ecosystem enables a high level of "smartness" that makes eliminating downtime easy.



#### Easy to start

Plug and play functionality makes it easy to install, setup and integrate hundreds of machines in a very short time.



#### Easy to use

Intuitive mobile app with awardwinning interface makes it easy to use – whether you are a beginner or an experienced user.



#### Easy to scale

Ease-of-use and affordability makes it easy to scale up and expand the scope of what you need at any time – in just a few steps.



#### Easy to decide

Complete overview of all machines and lubrication points, easy-to-understand alarms and automated analytics make it easy to know what to do next.



#### Easy to profit

Immediate reduction in downtime results in a quick ROI. Cost-efficiency also makes comprehensive, large-scale smart lubrication and condition monitoring affordable.

## SCHAEFFLER LIFETIME SOLUTIONS


### Keep your machines rolling

Schaeffler Lifetime Solutions is a full suite of industrial maintenance products, services and solutions for the entire machine lifetime. Designed with maintenance teams and plant managers in mind, the portfolio offers you everything you need to ensure that uninterrupted rhythm in your workshops and plants.

Regardless of whether you are working in food and beverage, pulp and paper, cement and mining – or any other industry. So that you can roll through the everyday knowing your machines are running smoothly.

Ready to roll?

www.schaeffler.de/en/lifetime-solutions



### Schaeffler Technologies AG & Co. KG

www.schaeffler.de/en/optime-c1 lifetime.solutions@schaeffler.com Tel. +49 2407 9149-66

Every care has been taken to ensure the correctness of the information contained in this publication but no liability can be accepted for any errors or omissions. We reserve the right to make technical changes.

© Schaeffler Technologies AG & Co. KG Issued: 2024, April
This publication or parts thereof may not be reproduced without our permission.